

Basculante

PA623S



32L



Opcional | En option | Optional



PA623DOS



*VC4


Variantes | Variantes | Alternatives




PA623D



PA623



Ref.		A	Ø B	H	H1
PA623	32L.	400 mm	320 mm	1465 mm	460 mm
PA623D	2×32L.	738 mm	320 mm	1465 mm	460 mm
PA623S	32L.	400 mm	320 mm	1465 mm	460 mm
PA623DOS	2×32L.	738 mm	320 mm	1465 mm	460 mm



Vaciado / vidage / Emptying / Despejo



Cubeta cilíndrica embutida y poste de Ø 60 mm de acero galvanizado, imprimación epoxi y pintura poliéster en polvo color negro forja. Anclaje recomendado: Mediante empotramiento en el suelo. Opcional: Con sombrero.

Corbeille cylindrique en tôle emboutie et poteau de Ø 60 mm en acier galvanisé, couche primaire époxy et thermolaquage polyester noir de forge. Ancrage recommandé : encastrement dans le sol. En option : avec protège-pluie.

Built-in cylindrical bin and Ø 60 mm galvanised steel post with epoxy primer coating and black wrought iron coloured polyester powder coated finish. Recommended anchoring: Embedded in the ground. Optional: Lid available.

Balde cilíndrico embutido e poste de Ø60 mm de aço galvanizado imprimação epóxi e pintura poliéster em pó cor preto forja. Fixação recomendada: colocado diretamente no solo. Opcional: com sombreiro.